

Product data sheet

1-gang push-button (insert), 1-pole, 1-way NO contact



Reference number

531 U

1-gang push-button 10 A / 250 V ~ (insert)

with screwless terminals for rigid wires up to 2.5 mm²

Can be converted into pull cord push-button by means of pull cord insert ref.-no. 34 or 34 KO5

without claws: ref.-no. with additional "E", e.g.: 531 EU

Illumination possible with lamp ref.-no. 90/95 (230 V), 96-.. (low voltage), or LED lamp ref.-no. 90-LED.. (230 V) or 961248 LED.. (low voltage).

Notice!

Installation only by persons with relevant electrical knowledge and experience!*) Use only with original JUNG product components approved for this article.

By inappropriate installation you endanger

- your own life,
- the life of the user of the electrical appliance.

By inappropriate installation you risk a high loss by damage, e.g. risk by fire. You assume personal liability in cause of injury to persons or damage of appliances. Please contact a skilled electrician!

*) Required technical knowledge for installation:

For installation, especially the following technical knowledge is required:

- the 5 important safety rules: disconnect from mains, secure against reconnecting, verify parts are free of voltage, ground and short-circuit, cover or block off adjacent live parts
- select adequate tools, measuring devices and personal protective equipment
- evaluate measuring results
- selection of the electrical installation material to secure switch-off conditions
- IP protection levels
- installation of the electrical installation material
- type of electric power grid (TN system, IT system) and the resultant connection terms (common grounding, protective ground, required additional action etc.)

Cradle to Cradle certified

Version:

1-pole, 1-way NO contact