M2249-2W 1/4



PRODUCT-DETAILS

M2249-2W OneTouch 7, LAN + Wi-Fi, white



General Information

M2249-2W 2/4

Extended Product Type M2249-2W 2TMA320051W0001 Product ID EAN 6955891822696 **Catalog Description** OneTouch 7, LAN + Wi-Fi, white

Central Control Panel for ABB-Welcome® (2-Wire) and ABB-free@home

Control, monitor, and manage your entire system with one device: switching, dimming, sliders, blinds, RGBW control, step switch, scene switch, display element, and audio control.

Free@home Functions:

Integrated System Access Point for a purely free@home wireless system. Allows commissioning and remote control of a ABB-free@home® wireless system.

Supports up to 150 free@home wireless devices.

Comes with an integrated free@home wireless antenna.

Free@home commissioning is done via a web interface or app.

No additional commissioning software is required. Easy free@home commissioning through Wi-Fi ad hoc mode.

Connects to the home network via Wi-Fi client mode or using a CAT cable (LAN adapter

More information on free@home commissioning and operation can be found in the system

manual and online user guide

Can also be used as a standalone free@home panel in combination with an external

System Access Point. The integrated System Access Point is not used when paired with an external System

Comes with an integrated room temperature controller and temperature sensor.

Displays the video feed from the outdoor station.

During conversations, a photo of the visitor can be captured and stored in memory. Three photos of the visitor are automatically stored in memory when door calls occur in your

Different ringtones can be set for door and floor calls, with five polyphonic tones available.

Adjustable ringtone volume.

Equipped with a hearing loop to feed the audio signal into hearing aids.

Features a hands-free function with adjustable volume.

Allows integration of ONVIF IP cameras. For integration into the myBuildingPortal.

App integration:

Enables the integration of a tablet or smartphone with installed OneApp/free@home next APP or Welcome App as a mobile indoor station for audio and video communication. Enables the integration of tablet or smartphone with installed OneApp/free@home next APF

for remote control of the free@home wireless system

Power Supply:

Via Busch-Welcome 2-wire bus

Alternatively, Power-over-Ethernet (PoE IEEE 802.3) or external power supply 20-32 VDC

(SELV).

Rated current: 400mA (24V DC).

Technical Details:

Screen size: 7' Display resolution: 1024x600

Screen: IPS

Dimensions (L x W x D): 128mm x 192mm x 17.5mm

For flush mounting with 42491F For surface mounting with 42491S-x

For Desktop mounting with 83506

Installation

Long Description

2TMU230000M0022 Instructions and Manuals

Mounting Type Flush Mounted Surface Mounted

Environmental

Ambient Air Temperature Operation 0 ... +45 °C Storage -25 ... +70 °C

Degree of Protection IP30 M2249-2W 3/4

Technical	
Data Sheet, Technical Information	2TMU230000M002
Communication Interface	LAN + Wi-F
Compatible Bus Systems	free@home wireles
Product Range	Welcom free@home Wireles
Fransmission Standard	
	Wireles Etherne
Connection Type	Wireless LAI RJ4:
Display Type	IPS Touch Displa
Ferminal Type	Screw Terminals, Pluqqable
Desim	
Design	Cimilanta DAL 004
RAL Number Color	Similar to RAL 9010 white
Dimensions	
Product Net Width	192 mr
Product Net Height	128 mi
Product Net Depth / Length	17.2 mi
Product Net Weight	379
Ordering	
E-Number (Finland)	281594
E-Number (Norway)	630748
Circular Value	
Environmental Product Declaration - EPD	9AKK108470A852
Material Compliance RoHS Information	2TMD081215X240
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
REACH Declaration	2TMD081215X240
REACH Information	False - does not contain substances > 0.1 mass percentag
Conflict Minerals Reporting Template CMRT)	9AKK108468A336
NEEE Category	Screens, Monitors, and Equipment Containing Screens Having a Surface Greater Than 100 cm
NEEE B2C / B2B	Business To Consume
Certificates and Declarations	
Cyber Security Software	2 ye:
,,so. socially control	2 year

M2249-2W 4/4

Support Period

Declaration of Conformity	2TMD081313X0189
- CF	

External Classifications and Standards

Accessories					
Identifier	Description	Туре	Quantity	Unit Of Measure	
2TMA320161W0001	Surface-mounted box, white	42491S-W	1	piece	
2TMA320161B0001	Surface-mounted box, black	42491S-B	1	piece	
2TMA320161B0002	Flush-mounted box, black	42491F	1	piece	
2TMA320161W0002	LAN adapter	5249C	1		

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow Door\ Entry\ \&\ Access\ Control\ Systems \rightarrow Welcome \rightarrow Indoor\ Stations$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow free@home \rightarrow System\ Infrastructure\ and\ Interfacing \rightarrow System\ Access\ Points$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow free@home \rightarrow User\ Operation \rightarrow Displays$









360