SA-M-4.16.2.2 1/4



PRODUCT-DETAILS

## SA-M-4.16.2.2

## SA-M-4.16.2.2 Switch Actuator, 4-fold 16 A, MDRC



| General Information   |   |
|-----------------------|---|
| Extended Product Type | SA-M-4.16.2.2   |
| Product ID            | 2CDG510025R0011   |
| EAN                   | 4053546111309   |
| Catalog Description   | SA-M-4.16.2.2 Switch Actuator, 4-fold 16 A, MDRC  |
| Long Description      | For switching 4 independent 127 V~/230 V~ loads. Each contact has a manual operation function independent of auxiliary voltage for additionally displaying the contact setting. The bus can be connected via enclosed terminal block. |

| Installation                         |                 |
|--------------------------------------|-----------------|
| Instructions and<br>Manuals          | 2CDG941253P0001 |
| Instructions and<br>Manuals (Part 2) | 2CDG941254P0001 |
| Wiring Diagram                       | 9AKK108467A6048 |
| Mounting Type                        | DIN-Rail        |

SA-M-4.16.2.2 2/4

| Environmental                          |                 |
|--|-----------------|
| Degree of Protection                   | IP20            |
| <br>Technical                          |                 |
|  |                 |
| Data Sheet, Technical<br>Information   | 2CKA000073B5511 |
| Contact Position<br>Indication         | ON / OFF        |
| Number of Outputs                      |                 |
| Number of LEDs                         |                 |
| Maximum Number of Switching Outputs    | -               |
| Compatible Bus Systems                 | free@home (TP   |
| Product Range                          | free@home       |
| Manual Operation                       | Yes             |
| Suitable for C-Load                    | No              |
| Number of Batteries                    |                 |
|  |                 |
| Electrical                             |                 |
| Voltage Range                          | 230 V AC        |
| Output Voltage (U <sub>out</sub> )     | 230 V AC        |
| Rated Current (In)                     | 16 A            |
| Maximum Switching<br>Current           | 16 A            |
| Maximum Switching Power                | 2500 W          |
| Power Loss                             | 4 W             |
|  |                 |
| Design                                 |                 |
| Color                                  | grey            |
|  |                 |
| Dimensions                             |                 |
| Width in Number of<br>Modular Spacings | <b>4.</b> C     |
| Product Net Width                      | 70 mm           |
| Product Net Height                     | 90 mm           |
| Product Net Depth / Length             | 63.5 mm         |
| Product Net Weight                     | 0.215 kg        |
| Built-In Depth (t <sub>2</sub> )       | 63.5 mm         |
| Dimension Diagram                      | 2CDC072033F0015 |
| Ordering                               |                 |
|  | 2020000         |
| E-Number (Finland)                     | 2830080         |
| E-Number (Norway)                      | 4549591         |

SA-M-4.16.2.2 3/4

| ABB EcoSolutions                                     | Ye   |
|--|--|
| EcoSolutions Profile                                 | 9AKK108470A243   |
|  |  |
| Circular Value                                       |  |
| Recyclability Rate of the<br>Product acc. to EN45555 | Design for Closing Resource Loops - Standard EN45555 - 36.6 %  |
| ABB Site Meeting Group<br>Waste To Landfill Target   | No non-hazardous waste is sent to a landf  |
| Extended Product<br>Lifetime                         | Product Durabilit Product Modularit Lifetime extension of customer's assets is made possible thanks to |
| Offered with Takeback                                | offering and the supporting service<br>Take Back for Recyclin  |
| Services   | Take back for Necycling  |
| Environmental Product<br>Declaration - EPD           | 9AKK108469A800   |
| Material Compliance                                  |  |
| RoHS Information                                     | 2CKA200000E778:  |
| RoHS Status  | Following EU Directive 2011/65/EI  |
| REACH Declaration                                    | 9AKK107492A190   |
| REACH Information                                    | True - contains substances > 0.1 mass percentag  |
| REACH Date   | 2024012  |
| Conflict Minerals<br>Reporting Template<br>(CMRT)    | 9AKK108468A336   |
| WEEE Category  | 5. Small Equipment (No External Dimension More Than 50 cm  |
| WEEE B2C / B2B                                       | Business To Consume  |
| Certificates and Declarations                        |  |
| Cyber Security Software<br>Support Period            | 2 yea  |
| Declaration of<br>Conformity - CE                    | 9AKK108467A603<br>2CKA100000E480   |
| Popular Downloads                                    |  |
| Time-Current   | 9AKK108467A604   |
| Characteristic Curve                                 | JAMMOOTOTAGGT  |
|  | rds  |
| ETIM 9   | EC001097 - Switch actuator for bus syster  |
| eClass   | V11.0 : 2714312  |
| UNSPSC   | 3125151  |
|  |  |

IDEA Granular Category Code (IGCC)

3268 >> Switch actuator

SA-M-4.16.2.2 4/4

## **Categories**

Low Voltage Products and Systems  $\rightarrow$  Building and Home Automation Solutions  $\rightarrow$  free@home  $\rightarrow$  Lighting Control  $\rightarrow$  Switch Actuators 16 A

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow free@home \rightarrow Standard\ Outputs \rightarrow Switch\ Actuators\ 16\ A$ 







