

MAA1050Y10



OTL50 gnybtas 1xAl/Cu 1,5-50mm² 1000V AC / 1500V DC g/ž

OTL50 gnybtas 1xAl/Cu 1,5-50mm² 1000V AC / 1500V DC g/ž

Prekės kodas	MAA1050Y10
EAN	4744397013835
ETIM klasė	EC000897
Gaminių serija	Universal terminals OTL
CN8 kodas	85369010
Vienetas	vnt
Pakuotės dydis:	48
Svoris (neto)	0.03 kg
Ilgis	0.05 m
Plotis	0.018 m
Gylis	0.043 m

Connectable conductor cross section fine-strand without cable end sleeve	1.5 - 35 mm ²
Connectable conductor cross section fine-strand with cable end sleeve	1.5 - 35 mm ²
Connectable conductor cross section solid-core	Nežinoma
Connectable conductor cross section multi-wired	1.5 - 50 mm ²
Rated current I _n	160 A
Rated voltage	1500 V
Type of electrical connection 1	Screw connection
Type of electrical connection 2	Netaikoma
Number of levels	1
Number of clamp positions per level	2
Suitable for conductor material	-
Mounting method	DIN rail (top hat rail) 35 mm
Material insulation body	Thermoplastic
Operating temperature	-25 - 80 °C
Inflammability class of insulation material according to UL94	V0
Width	18 mm
Height	43 mm
Depth	50 mm
Explosion-tested version 'Ex e'	Ne
Closing plate required	Ne
Colour	Green/yellow
Internally connected stages	Taip

